

Please type a plus sign (+) inside this box → ☐

PTO/SE/05 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 22-0009 Total Pages 34

First Named Inventor or Application Identifier

Donald C. Wilcoxson, et al.

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Express Mail Label No. EE234200576US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 27]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets 4]
4. ☐ Oath or Declaration [Total Pages 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☒ 37 CFR 3.73(b) Statement ☒ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application, Statement(s) ☐ Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information.

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____/_____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here):

or ☒ Correspondence address below

NAME	Patent Counsel TRW Inc.				
ADDRESS	Law Dept. One Space Park, Bldg. E2/6072				
CITY	Redondo Beach	STATE	CA	ZIP CODE	90278
COUNTRY	USA	TELEPHONE	310.812.4910	FAX	310.812.2687

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTALNote: Effective October 1, 1997.
Patent fees are subject to annual revision.**TOTAL AMOUNT OF PAYMENT** (\$ 830.00)**Complete if Known**

Application Number	
Filing Date	November 6, 1998
First Named Inventor	Donald C. Wilcoxson
Group Art Unit	Not Assigned
Examiner Name	Not Assigned
Attorney Docket Number	22-0009

METHOD OF PAYMENT (check one)

- 1.
- ☒
- The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:

Deposit Account Number	20-1515
Deposit Account Name	TRW Inc.

- ☒
- Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17
- ☐
- Charge the Issue Fee Set in 37 CFR 1.18 at the Mailing of the Notice of Allowance

- 2.
- ☐
- Payment Enclosed:
-
- ☐
- Check
- ☐
- Money Order
- ☐
- Other

FEE CALCULATION**1. FILING FEE**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
101 790	201 395	Utility filing fee	790.00
106 330	206 165	Design filing fee	
107 540	207 270	Plant filing fee	
108 790	208 395	Reissue filing fee	
114 150	214 75	Provisional filing fee	
SUBTOTAL (1)			(\$ 790.00)

2. CLAIMS

Total Claims	Extra	Fee from below	Fee Paid
20 - 20 = 0	X		0
Independent Claims 3 - 3 = 0	X		0
Multiple Dependent Claims	X		

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
103 22	203 11	Claims in excess of 20
102 82	202 41	Independent claims in excess of 3
104 270	204 135	Multiple dependent claim
109 82	209 41	Reissue independent claims over original patent
110 22	210 11	Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$ 0)**FEE CALCULATION (continued)****3. ADDITIONAL FEES**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
105 130	205 65	Surcharge - late filing fee or oath	
127 50	227 25	Surcharge - late provisional filing fee or cover sheet	
139 130	139 130	Non-English specification	
147 2,520	147 2,520	For filing a request for reexamination	
112 920*	112 920*	Requesting publication of SiR prior to Examiner action	
113 1,840*	113 1,840*	Requesting publication of SiR after Examiner action	
115 110	215 55	Extension for reply within first month	
116 400	216 200	Extension for reply within second month	
117 950	217 475	Extension for reply within third month	
118 1,510	218 755	Extension for reply within fourth month	
128 2,060	228 1,030	Extension for reply within fifth month	
119 310	219 155	Notice of Appeal	
120 310	220 155	Filing a brief in support of an appeal	
121 270	221 135	Request for oral hearing	
138 1,510	138 1,510	Petition to institute a public use proceeding	
140 110	240 55	Petition to revive - unavoidable	
141 1,320	241 660	Petition to revive - unintentional	
142 1,320	242 660	Utility issue fee (or reissue)	
143 450	243 225	Design issue fee	
144 670	244 335	Plant issue fee	
122 130	122 130	Petitions to the Commissioner	
123 50	123 50	Petitions related to provisional applications	
126 240	126 240	Submission of Information Disclosure Stmt	
581 40	581 40	Recording each patent assignment per property (times number of properties)	40.00
146 790	246 395	Filing a submission after final rejection (37 CFR 1.129(a))	
149 790	249 395	For each additional invention to be examined (37 CFR 1.129(b))	
Other fee (specify) _____			
Other fee (specify) _____			

* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$ 40.00)**SUBMITTED BY**

Typed or Printed Name: Michael S. Yatsko

Signature: *Michael S. Yatsko*

Date: 11/6/98

Complete (if applicable)

Reg. Number: 28,135

Deposit Account User ID: 2165

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

CERTIFICATE OF MAILING

Express Mail Mailing Label No. EE234200576US

Date of Deposit 11/6/98

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, DC 20231.

Mailer Lorna L. Schott

(signature)

Mailer

(print)

**INTERFERENCE MANAGEMENT
OF A
PROCESSING COMMUNICATIONS SATELLITE**

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to a communications system and, more particularly, to a method for interference management of a processing communications satellite to reduce intra-system interference in a satellite based cellular communications system.

2. Discussion of the Related Art

In satellite based cellular communications systems, a central terrestrial control processor or network operations center (NOC) generally controls one or more communications satellites operating within the communications system. Each communications satellite within the communications system services multiple users located in

09187370 " 440668
369077 04E8T60

multiple geographic areas known as ground cells. The communications satellites receive and transmit data signals to and from the multiple users located at the different positions within the separate ground cells in a point-to-point or point-to-multipoint manner. In a frequency division multiple access (FDMA)/time division multiple access (TDMA) communications system, signals on the same frequency, polarization and time slot are generally reused by different users within spatially separated ground cells because of bandwidth constraints, in order to increase the overall capacity of the system.

However, a disadvantage to users sharing frequency, polarization and time slots is that interference is created between the different users in the spatially separated ground cells. This interference may or may not be significant depending on the antenna beam patterns for the particular communications satellite and on the overall system design parameters. User interference may also be caused from multiple users utilizing adjacent frequencies near the boundaries between ground cells when the users are not ideally contained or restricted to their assigned frequency channels. Moreover, users assigned opposite polarizations but overlapping frequencies can also experience mutual interference since the transmit and receive antennas between the user and communications satellite cannot maintain perfect orthogonality between right-hand circularly polarized (RHCP) and left-hand circularly polarized (LHCP)

signals. In addition, other orthogonality destroying effects may further be caused by rain induced depolarization of the data signals.

In general, the above-noted interference is magnified in conventional satellite based cellular communications systems. The reason for this is that conventional satellite based cellular communications systems simply assign user frequencies, polarizations and time slots based on a non-adaptive adhoc scheme. These schemes generally are performed on a first come first serve basis using only random selection of user frequencies, polarizations (if applicable) and time slots between the various users. Such conventional satellite based cellular communications systems have much greater levels of intra-system interference and thus, reduced traffic carrying capacity and reduced overall efficiency.

What is needed then is a method for interference management of a processing communications satellite which does not suffer from the above mentioned disadvantages. This will, in turn, provide a satellite based cellular communications system which utilizes intelligent frequency, polarization and time slot assignments; reduces intra-system interference; provides a communications uplink which reduces the required transmit power, terminal complexity and cost; provides a communications downlink which reduces the communications satellite size, weight and power consumption; provides a reduced cost per beam based upon the reduced satellite

size, weight and power consumption; provides service to more geographic regions for a given size communications satellite; provides more traffic carrying capacity; provides greater systems revenues; and provides improved service quality to the end users. It is, therefore, an object of the present invention to provide a communications system which utilizes a method for interference management of a processing communications satellite.

SUMMARY OF THE INVENTION

In accordance with the teachings of the present invention, a satellite based cellular communications system for servicing multiple user terminals and a method for interference management of the processing communications satellite is provided. The satellite based cellular communications system minimizes intra-system interference between multiple user terminals by allocating particular connection parameters to each user terminal based upon accessing multiple communications system parameters.

In one preferred embodiment, a method for interference management of a processing communications satellite serving multiple user terminals in a satellite based cellular communications system is disclosed. The method includes receiving a request for service from a user terminal. With this request, at least one communications system parameter is accessed. Upon accessing the

communications system parameter, at least one connection parameter to minimize intra-system interference based upon the one communications systems parameter accessed is determined for the user terminal. Once determined, allocation of this connection parameter to the user terminal is made. The user terminal then makes a communications connection with the processing communications satellite using the connection parameter.

In another preferred embodiment, a satellite based cellular communications system for servicing multiple user terminals includes at least one processing communications satellite. The processing communications satellite supports communications uplinks and communications downlinks between multiple user terminals. A network operations center having a central control processor communicates with the processing communications satellite on the communications uplinks and the communications downlinks. The central control processor minimizes intra-system interference between the multiple user terminals by allocating a connection parameter to each user terminal based upon accessing a plurality of communications system parameters.

In yet another preferred embodiment, a method for interference management of a communications system servicing multiple users includes receiving a request for service from a user terminal. A plurality of communications system parameters is then accessed and

09187370-110698

a frequency channel and time slot allocation to minimize intra-system interference based upon the plurality of communications system parameters is determined for the user terminal. The frequency channel and time slot are allocated to the user terminal. The user terminal thereafter makes a communications connection using the frequency channel and time slot parameter. The frequency channel and time slot parameter is periodically redetermined for the user terminal to continue to minimize intra-system interference.

The use of the present invention provides a satellite based cellular communications system for servicing multiple user terminals which uses a method for interference management of a processing communications satellite in the communications system. As a result, the aforementioned disadvantages associated with the current communications systems have been substantially reduced or eliminated.

BRIEF DESCRIPTION OF THE DRAWINGS

Still other advantages of the present invention will become apparent to those skilled in the art after reading the following specification and by reference to the drawings in which:

Figure 1 is an overall satellite based cellular communications system block diagram;

Figure 2 is a detailed block diagram of a communications uplink between user terminals positioned within multiple ground cells and a processing communications satellite;

Figure 3 is a detailed block diagram of a communications downlink between the processing communications satellite and the user terminals positioned within the multiple ground cells; and

Figure 4 is a detailed flow diagram of a method for interference management of a processing communications satellite according to the teachings of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

The following description of the preferred embodiment concerning a method for interference management of a processing communications satellite to reduce intra-system interference in a satellite based cellular communications system is merely exemplary in nature and is not intended to limit the invention or its application or uses. Moreover, while the invention is described in detail below with respect to a satellite based cellular communications system, those skilled in the art will recognize that the method for interference management of a processing communications satellite may be used with various other centrally controlled communications systems as well.

Referring to Figure 1, a satellite based cellular communications systems 10 for supporting multiple users located in multiple geographic areas or ground cells is shown. The communications system 10 includes one or more processing communications satellites 12 operating generally in a geosynchronous orbit. Each communications satellite 12 supports multiple user terminals 14 positioned within various defined ground cells, further discussed herein. Each communications satellite 12 receives data signals from the user terminals 14 on communications uplinks 16 and transmits data signals to the user terminals 14 on communications downlinks 18. Each user terminal 14 transmits data signals on the communications uplinks 16 and receives data signals on the communications downlinks 18, via an antenna 20. Each communications satellite 12 receives and transmits the data signals on the communications uplinks 16 and the communications downlinks 18, via a multi-beam antenna 22 or any other appropriate antenna to service the required coverage region.

The satellite based cellular communications system 10 also includes a network operations center (NOC) 24 which includes a central control processor 26. The network operations center 24 generally controls the overall operations of each communications satellite 12 utilizing the communications uplink 16 and the communications downlink 18, via an antenna 28. These overall

09187370-110698
369077-02E2860

operations include maintenance of the geosynchronous orbit, positioning of solar collectors 30, initializing satellite system parameters, user billing, as well as other operational controls which are all well known in the art. The central control processor 26 of the network operations center 24 is preferably a general purpose programmable computer, a current example of which is a Sun Microsystems computer, or any other appropriate computer depending on the computational power required. The central control processor 26 also controls the interference management of each processing communications satellite 12 to reduce intra-system interference in the satellite based cellular communications 10 according to the teaching of the preferred embodiment of the present invention.

Referring now to Figure 2, a communications uplink 16a between a user terminal 14a and a processing communications satellite 12 is shown operating when no interference management is being performed. The communications satellite 12 services the coverage region 30 which includes multiple ground cells 34 represented by each hexagonal region. Each of the ground cells 34 is represented by a hexagonal shaped region 34 which are the regions each individually illuminated by one antenna beam from the multi-beam antenna 22 on the communications satellite 12. The coverage region 30 is shown utilizing what is known as a 4-to-1 re-use where

the coverage region 30 is separated into one of four types of ground cells 32a-32d. Each of the ground cells 34 having the same shading operate within the same frequency band. Within each particular frequency band, many different frequency channels are available to user terminals 14 operating within these ground cells 34.

For example, each of the ground cells 32a may be allocated a first 100 MHz frequency band that is divided into 175 frequency channels. In this way, the user terminal 14a within the ground cell 32a is allocated one of the 175 frequency channels and at least one of the time slots allocated to that particular channel. Similarly, each of the ground cells 32b may be allocated a second 100 MHz frequency band, each of the ground cells 32c may be allocated a third 100 MHz frequency band, and each of the ground cells 32d may be allocated a fourth 100 MHz frequency band. Therefore, in this example, a 400 MHz frequency band is split into four different 100 MHz frequency bands where each group of ground cells 32a-32d is allocated one of the four different 100 MHz frequency bands, each containing 175 separate frequency channels and multiple time slots. In other words, all of the ground cells identified as 32a will be operated within the same 100 Mhz frequency band having the same 175 frequency channels available and so forth throughout each set of ground cells 34 within the coverage region 30.

Referring again to Figure 2, user terminal 14a in ground cell 32a is operating within the first 100 MHz frequency band and say, for example, channel one within this 100 MHz frequency band. User terminal 14a is also bursting on and off within a particular time slot for channel one within the 100 MHz frequency band. User terminal 14a may also use additional channels within the 100 MHz frequency band and/or additional time slots depending on how much bandwidth the user terminal 14a requires to transmit all its data, via the communications uplink 16a. The communications uplink 16a originating from user 14a is directed into a main beam 36 of the multi-beam antenna 22 that is servicing ground cell 32a. Main beam 36 also includes multiple sidelobes 38.

Secondary energy or co-channel interference (CCI) 16b is also shown originating from user terminal 14a. The co-channel interference 16b is received in the sidelobes 40 of main beam 42 which services the other central ground cell 32a where user terminal 14b is located. The reason that the co-channel interference 16b occurs is because the multi-beam antenna 22 for the communications satellite 12 is not able to control its reception characteristics perfectly. In other words, the user terminal 14a is transmitting energy to at least both the main beam 36 and the sidelobes 40 of the multi-beam antenna 22. This energy is coming into the sidelobes 40 at a lower power level, but this lower power level is still seen as interference to

the user terminal 14b and its communications uplink 16c. This interference is created by re-use of the same frequency band, channel and time slot by user terminals 14a and 14b. It should further be noted that additional uplink co-channel interference 16b may be created with other users operating within other ground cells 32a which utilize the same frequency band, channel and time slots as the user terminals 14a and 14b. This interference and signal degradation is what the interference management procedure minimizes.

Referring now to Figure 3, downlink co-channel interference (CCI) 18b from a communications downlink 18a between the communication satellite 12 and user terminals 14a and 14b is shown. In general, each of the communications downlinks 18 from the communications satellite 12 to the multiple user terminals 14 within each group of ground cells 32a-32d operate on a single carrier frequency, however this carrier may or may not be gated off at specified times. In other words, all of the ground cells 32a operate on a first carrier frequency, all of the ground cells 32b operate on a second carrier frequency and so forth. The reason for the single carrier frequency being used for each group of ground cells 32a-32d is because of the limited power constraints associated with operating the communications satellite 12. Accordingly, since communications downlink 18a and 18c are operating with the same carrier frequencies, co-channel interference 18b is generated from sidelobes

38 of main beam 36 which are received by user terminal 14b, when both carriers are gated on at the same time.

In order to minimize or eliminate communications uplink co-channel interference 16b and communications downlink co-channel interference 18b, an adaptive intelligent interference management method will be performed by the central control processor 26 in the network operations center 24. With reference to Figure 4, a detailed flow chart on this method or routine 50 for interference management of the processing communications satellite 12 within the satellite based cellular communications system 10 is shown. The routine 50 begins with start block 52 where the routine 50 is initialized within the central control processor 26. Once initialized, the routine 50 then enters the user request for service block 54 where either a single user terminal 14 or multiple user terminals 14 request service. These requests are transmitted through a dedicated channel on the communications uplink 16 which is received by the communications satellite 12 and transferred to the network operations center 24 on the communications downlink 18 for processing by the central control processor 26.

Each user terminal 14 requesting service will provide its user ID which will identify the physical location of the user terminal 14 within the ground cell 34, the bandwidth required by the user terminal 14 to transmit all of its data, the type of user terminal 14 or priority of the

user terminal 14 depending upon its fee schedule, and how much error correction encoding the user terminal 14 intends to be performing to provide an indication as to how much interference the user terminal 14 can handle. Once the user terminal 14 or multiple user terminals 14 make a request for service 54, the routine 50 steps to a parameter assignment block 56 which determines appropriate connection parameter assignments for each user terminal 14 to minimize interference for all the active user terminals 14 based upon various known input communications system parameters. These connection parameter assignments 56 may include setting the frequency channel, time slot, polarization, error correction encoding level, and power level allocations for each user terminal 14.

The known input communications system parameters which may be accessed by the parameter assignment block 56 are user database parameters 58, antenna pattern parameters 60, spacecraft/antenna pointing error parameters 62 and link condition database parameters 64. The user database parameters set forth in block 58 identify all of the current user terminals 14 active in the communications system 10, including where in each ground cell 34 the user terminals 14 are located, what frequencies and time slots the user terminals 14 are operating on, the power levels transmitted by the user terminals 14, the error correction encoding used by each

terminal 14, and the particular class of each user terminal 14 based upon fee schedule priorities.

5 The antenna pattern parameters set forth in block 60 identify the illumination patterns from the multi-beam antenna 22 positioned on the communications satellite 12. These illumination parameters include positioning of the individual main beams which service each ground cell 34, as well as the positioning of the sidelobes for each of these main beams.

10 The spacecraft/antenna pointing error parameters in block 62 set forth any antenna offset errors which may occur due to movement of the multi-beam antenna 22 during the geosynchronous orbit of the communications satellite 12. In other words, thermal effects, solar effects and solar wind may cause the communications satellite 12 to slightly move, shift, or rotate in its geosynchronous orbit, thereby
15 causing the multi-beam antenna 22 to illuminate each ground cell 34 slightly off its desired pattern.

20 The link condition database parameters in block 64 identify the physical conditions between each active user terminal 14 in the communications system 10 and the communications satellite 12. These conditions include any adverse weather conditions, such as rain which may create attenuation of the uplink or downlink signals. These link condition database parameters 64 are generally provided to the communications satellite 12 from each user terminal 14 based

upon the user terminal 14 monitoring its current link condition and periodically sending these parameters to the central control processor 26 in the network operations center 24, via a communications uplink 16 and a communications downlink 18 through communications satellite 12.

Each of the connection system parameters set forth in the user database 58, antenna patterns 60, spacecraft/antenna pointing error 62 and link condition database 64 are generally stored in a central memory location that is accessed by the central control processor 26. The central control processor 26 will perform the connection parameter assignments 56 based upon the particular assignment algorithm utilized by the parameter assignment block 56.

One of the least computationally-intensive assignment algorithms which may be utilized by the parameter assignment block 56 is based upon using a single input communications system parameter from the user database 58 directed to where each active user terminal 14 is currently operating. This assignment algorithm will essentially compare all the current frequency channels and time slots that are active and determine the distance between any two user terminals 14, whereby the parameter assignment block 56 would select the appropriate frequency channel and time slots for each user terminal 14 to provide the maximum distances between user terminals 14 operating on the same frequency channel and time slot. Such an

assignment algorithm may readily be constructed by those skilled in the art. In this way, the user terminals 14 requesting service 54 would be allocated the appropriate frequency channel and time slot connection parameters based upon where each active user terminal 14 is located. This frequency channel and time slot allocation is made by the central control processor 26 and occurs at the frequency and time slot allocation block 66. Once the connection parameter allocation is made by the central control processor 26, there is a time delay 68 which occurs because of the transfer time required to transfer the parameter allocations to the particular user terminals 14, via communications uplink 16 and communications downlink 18 through communications satellite 12.

After the time delay 68, the user terminals 14 which have been allocated their particular connection parameters, such as the frequency channel and time slot, now make their communication connections and begin data transfers under these connection parameters. The routine 50 then steps to decision block 70 which determines whether or not the connection is still active for the particular user terminals 14 which have been allocated their frequency channel and time slots. Should the connection no longer be active, the routine steps to the update database block 72 which updates the user database 58, antenna patterns 60, spacecraft/antenna pointing error 62 and link condition database 64 to identify that the particular

user terminal 14 is no longer active in the communications system 10.

Thereafter, routine 50 subsequently steps to the end block 74 and ends the routine 50 for the particular user terminals 14.

Should the connection still remain active 70, the routine 50 then returns to the parameter assignment block 56 in order to recalculate frequency channel and time slot assignments for each of the user terminals 14 active on the system, based upon any updated parameters set forth in the user database 56, antenna pattern 60, spacecraft/antenna pointing error 62 and link condition database 64 which may have changed during the active connection 70.

Should additional computational power be available in the central control processor 26, more detailed assignment algorithms may be used to provide the adaptive intelligent connection parameter assignments 56 which are selected on a deterministic controlled fashion using additional connection system parameters from blocks 58-64. For example, the assignment algorithm may also take into account the distances between the active user terminals 14 and the known antenna patterns from antenna pattern block 60. In this way, the assignment algorithm will actually calculate what type of interference may occur by allocating particular frequency channels and time slots for the particular user terminals 14 in light of the antenna patterns from the multi-beam antenna 22 positioned on the communications satellite 12. This calculation is based upon where

the main beams and sidelobes would be located relative to the user terminals 14. Moreover, should further accuracy in this determination be desired, the spacecraft/antenna pointing error 62 may be taken into account to get a more accurate interference mapping based upon corrected antenna pattern parameters 60.

Other assignment algorithms may also take into account the link condition database parameters 64 which identify whether or not any of the requesting user terminals 14 and active user terminals 14 are operating in a communications link through severe weather. Frequency channel and time slot allocations may also take into account the priority of the particular user terminal 14 directed to what fees the user terminal 14 is, in fact, paying relative to other user terminals 14. Each of these assignment algorithms may be readily constructed by those skilled in the art depending upon the computational power available for the particular communications system 10.

The above description of the routine 50 generally relates to assigning communications uplinks 16 for the various user terminals 14 in an FDMA/TDMA communications uplink. Should a communications downlink 18 be utilized where the communications downlinks 18 operate at different frequencies and time slots similar to the communications uplinks 16, the routine 50 for the communications downlink 18 is substantially the same. Should the communications

downlink 18 operate, as shown in Figure 3, such that a single carrier frequency is used for each particular set of ground cells 34, the parameter assignment block 56 may allocate communication downlinks 18 on a time varying basis such that the frequency and time slot allocation block 66 will simply be replaced with a time varying parameter allocation block 66 or any other appropriate connection parameter allocation. In other words, referring to Figure 3, should the same carrier frequency be utilized for the communication downlink 18a and the communication downlink 18c, a time allocation may be set between user terminals 14a and 14b such that the communication downlink 18a is on for a certain period of time and off when communication downlink 18c is on, thereby eliminating a co-channel interference 18b between user terminals 14a and 14b.

The routine 50 for interference management of the various communications satellites 12 minimizes or eliminates intra-system interference within the communications system 10 by using an adaptive intelligent connection parameter allocation for each user terminal 14 based upon at least one communication system input parameter, such as user terminal locations. Should further interference minimization be desired, additional known input parameters may be accessed by the parameter assignment block 56 from the user database parameters 58, antenna pattern parameters 60, spacecraft/antenna pointing error parameters 62 and link

condition database parameters 64 with the only limiting constraint being the amount of computational power available in the central control processor 26. This computational power will vary depending on whether a general purpose computer, such as a Sun Microsystems computer, is utilized versus a mainframe computer or supercomputer. Any of the noted assignment algorithms may then be readily prepared by someone skilled in the art based upon the computational power available and the desired interference minimization required between user terminals 14.

The foregoing discussion discloses and describes merely exemplary embodiments of the present invention. One skilled in the art will readily recognize from such discussion, and from the accompanying drawings and claims, that various changes, modifications and variations can be made therein without departing from the spirit and scope of the invention as defined in the following claims.

CLAIMSWhat is Claimed is:

1 1. A method for interference management of a
2 processing communications satellite serving multiple user terminals in
3 a satellite based cellular communications system, said method
4 comprising:

5 receiving a request for service from a user terminal;

6 accessing a communications system parameter;

7 determining a connection parameter to minimize intra-
8 system interference based upon the communications system
9 parameter for the user terminal;

10 allocating the connection parameter to this user
11 terminal; and

12 making a communications connection with the
13 processing communication satellite by the user terminal using the
14 connection parameter.

1 2. The method as defined in claim 1 further
2 comprising accessing a plurality of communications system
3 parameters.

1 3. The method as defined in claim 2 wherein said
2 plurality of communications system parameters includes active user
3 terminal parameters.

1 4. The method as defined in claim 3 wherein said
2 active user terminal parameters includes locations of each active user
3 terminal and frequency channels and time slots allocated to active
4 user terminals.

1 5. The method as defined in claim 2 wherein said
2 plurality of communications system parameters includes user
3 database parameters, antenna pattern parameters,
4 spacecraft/antenna pointing error parameters, and link condition
5 database parameters.

1 6. The method as defined in claim 1 further
2 comprising monitoring if the communications connection is still active.

1 7. The method as defined in claim 6 further
2 comprising redetermining the connection parameter for the user
3 terminal based upon an updated communications system parameter.

1 8. The method as defined in claim 1 wherein the
2 one connection parameter is a frequency channel.

1 9. The method as defined in claim 1 wherein the
2 connection parameter is a time slot.

1 10. The method as defined in claim 1 further
2 comprising updating the communications system parameter after the
3 communications connection ends.

1 11. A satellite based cellular communications system
2 for servicing multiple user terminals, said satellite based cellular
3 communications system comprising:

4 a processing communications satellite, said processing
5 communications satellite supporting communications uplinks and
6 communications downlinks between the multiple user terminals; and

7 a network operations center having a central control
8 processor, said network operations center communicating with said
9 processing communications satellite on said communications uplinks
10 and said communications downlinks, said central control processor
11 minimizes intra-system interference between the multiple user
12 terminals by allocating a connection parameter to each user terminal
13 based upon accessing a plurality of communications system
14 parameters.

1 12. The satellite based cellular communications
2 system as defined in claim 11 wherein said processing
3 communications satellite supports the multiple user terminals via a
4 multi-beam antenna.

1 13. The satellite based cellular communications
2 system as defined in claim 11 wherein said central control processor
3 allocates a frequency channel and time slot for each user terminal
4 based upon locations of active user terminals.

1 14. The satellite based cellular communications
2 system as defined in claim 11 wherein said plurality of
3 communications system parameters includes user database
4 parameters, antenna pattern parameters, spacecraft/antenna pointing
5 error parameters, and link condition database parameters.

1 15. The satellite based cellular communications
2 systems as defined in claim 11 wherein said central control processor
3 periodically re-allocates said connection parameters to each user
4 terminal based upon an updated plurality of communications system
5 parameters.

1 16. A method for interference management of a
2 communications system servicing multiple user terminals, said
3 method comprising:

4 receiving a request for service from a user terminal;

5 accessing a plurality of communications system
6 parameters;

7 determining a frequency channel and time slot
8 parameter allocation for the user terminal to minimize intra-system
9 interference based upon the plurality of communications system
10 parameters;

11 allocating the frequency channel and time slot
12 parameter to the user terminal;

13 making a communications connection by the user
14 terminal using the frequency channel and time slot parameter; and
15 periodically redetermining the frequency channel and
16 time slot parameter allocation for the user terminal to continue to
17 minimize intra-system interference.

1 17. The method as defined in claim 16 further
2 comprising redetermining the frequency channel and time slot
3 allocation after a determination is made that the communications
4 connection is still active.

1 18. The method as defined in claim 16 comprising
2 accessing the plurality of communications system parameters from a
3 user database, antenna pattern database, spacecraft/antenna
4 pointing error database and link condition database.

1 19. The method as defined in claim 18 further
2 comprising updating the databases after the communication
3 connection has ended.

1 20. The method as defined in claim 16 comprising
2 including within the plurality of communications system parameters
3 location of active user terminals and frequency channel and time slots
4 allocated to the active user terminals.

INTERFERENCE MANAGEMENT OF A PROCESSING**COMMUNICATIONS SATELLITE****ABSTRACT OF THE DISCLOSURE**

A satellite based cellular communications system (10) for servicing multiple user terminals (14) is provided. The satellite based cellular communications system (10) includes at least one processing communications satellite (12) which supports communications uplinks (16) and communications downlinks (18) between multiple user terminals (14). A network operations center (24) having a central control processor (26) communicates with the processing communication satellite (12) on the communications uplinks (16) and the communications downlinks (18). The central control processor (26) minimizes intra-system interference between the multiple user terminals (14) by allocating a connection parameter to each user terminal (14) based upon accessing a plurality of communication system parameters.




Figure 1





Figure 2

downlink



Downlink Co-Channel Interference (CCI) from satellite into ground cells that share the same frequency and polarization.

Figure 3




Figure 4

Docket No. 22-0009

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled INTERFERENCE MANAGEMENT OF A PROCESSING COMMUNICATIONS SATELLITE the specification of which

X is attached hereto

_____ was filed on _____ as Application
Serial No. _____ and was amended on
_____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

<u>NONE</u>	_____	_____	_____	_____
(Number)	(Country)	(Day/Mo./Yr. Filed)	Yes	No

Docket No. 22-0009

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>NONE</u> (Number)	<u> </u> (Country)	<u> </u> (Day/Mo./Yr. Filed)	<u> </u> (Status)
-------------------------	--	--	---

I hereby appoint as principal attorneys:

Robert W. Keller, Reg. No. 25,347
Michael S. Yatsko, Reg. No. 28,135
Connie M. Thousand, Reg. No. 43,191
G. Greg Schivley, Reg. No. 27,382

each with full power to prosecute this application, to transact all business in the United States Patent and Trademark Office connected therewith, and to appoint and revoke associate and substitute associate attorneys.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Address all telephone calls to: (310) 812-4910

Address all correspondence to: PATENT COUNSEL
TRW Inc.
Space & Electronics Group
One Space Park, E2/6072
Redondo Beach, California 90278

Docket No. 22-0009

Full name of first or sole inventor Donald C. Wilcoxson
Inventor's signature Donald C. Wilcoxson Date: 28 Oct 98
Residence Redondo Beach, California
Citizenship United States
Post Office Address 1803 Clark Lane, #A, Redondo Beach, California 90278

Full name of second inventor Eldad (NMI) Perahia
Inventor's signature Eldad Perahia Date: 28 Oct 98
Residence Hermosa Beach, California
Citizenship United States
Post Office Address 1600 Ardmore Avenue, #228, Hermosa Beach, California 90254

Full name of third inventor Gregory S. Caso
Inventor's signature Gregory Scott Caso Date: 2 Nov 1998
Residence Hermosa Beach, California
Citizenship United States
Post Office Address 1533 Golden Avenue, Hermosa Beach, California 90254

Full name of fourth inventor David G. Klemes
Inventor's signature David G. Klemes Date: 6 Nov 1998
Residence Culver City, California
Citizenship United States
Post Office Address 10727 Kelmores Street, Culver City, California 90230